

# TCA 32 Centrifugal Pump



200 Newsome Drive  
Yorktown, VA 23693  
1-800-535-4243  
www.Travaini.com



<b>Head Capacity</b>	16 to 330 Feet
<b>Capacity</b>	Up to 175 USGPM
<b>Features</b>	Open impeller design allows for the handling of highly abrasive liquids
<b>Shaft Sealing</b>	Mechanical seal (std) Double mechanical seal Packed stuffing box
<b>Options</b>	Bareshaft pump Coupled to electric motor Spacer coupling Monoblock
<b>Temperature</b>	GS & RA: -4°F-536°F A3, HC, & DU: -40°F-536°F

## Technical Data

PUMP TYPE		TCA32-125		TCA32-160		TCA32-200	
Head, max	Ft	29	119	50	205	78	330
Capacity, max	GPM	52	110	73	140	85	170
Speed	RPM	1750	3500	1750	3500	1750	3500

## Standard Materials of Construction\*\*

Part No.	Description	GS	RA	A3	HC	DU	
102	Pump casing	Ductile iron			Hastealloy C	ASTM-CN7M	
135	Wear plates	-	Cast iron				
161	Casing cover	Ductile iron					
210	Shaft	Stainless steel AISI 316				Incoloy 825	
230	Impeller					ASTM-CN7M	
330	Bearing housing	Cast iron					
524	Shaft sleeve	Stainless steel AISI 316			Hastealloy C	Incoloy 825	

## Model Designation

TCA32-200 A/1X-C/A3	
T	Travaini manufacturer
C	Monostage centrifugal pump
A	Open impeller
32	Discharge flange size (mm)
200	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
1X	Constructive project number
C	Shaft sealing: C—Single mechanical seal 2C— Double mechanical seal
A3	Materials of construction

\*\*Special materials available upon request  
--For further information please consult Travaini Pumps USA.

REF:	JGJ/RR	Date	3/17/2015	Nº:	100198.000
------	--------	------	-----------	-----	------------