

TCHM 65 Centrifugal Pump



200 Newsome Drive
Yorktown, VA 23693
1-800-535-4243
www.Travaini.com



Head Capacity	10 to 300 Feet
Capacity	Up to 810 USGPM
Features	Closed impeller design for use with clean or muddy liquids
Shaft Sealing	Mechanical seal (standard) Double mechanical seal Stuffed packing box
Options	Bareshaft pump Coupled to electric motor Monoblock
Temperature	GS & RA: -20°C-280°C A3, HC, & DU: -40°C-280°C

Technical Data

PUMP TYPE		TCHM65-125		TCHM65-160		TCHM65-200		TCHM65-250	
Head, max	Ft	31	125	50	200	73	300	118	
Capacity, max	GPM	310	675	390	750	400	810	375	
Speed	RPM	1750	3500	1750	3500	1750	3500	1750	

Standard Materials of Construction**

Part No.	Description	GS	RA	A3	HC	DU
102	Pump casing	Ductile iron			Hastealloy C	ASTM-CN7M
135	Wear plates	-	Cast iron			
161	Casing cover	Ductile iron				
210	Shaft	Stainless steel AISI 316				Incoloy 825
230	Impeller					ASTM-CN7M
330	Bearing housing	Cast iron				
524	Shaft sleeve	Stainless steel AISI 316			Hastealloy C	Incoloy 825

Model Designation

TCHM65-200 A/1X-C/A3	
T	Travaini manufacturer
C	Monostage centrifugal pump
H	Closed impeller
M	Monoblock Construction
65	Discharge flange size (mm)
200	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
1X	Constructive project number
C	Shaft sealing: C—Single mechanical seal 2C— Double mechanical seal
A3	Materials of construction

**Special materials available upon request

--For further information please consult Travaini Pumps USA.

REF:	JM/CGZ	Date	8/13/2019		Nº:
------	--------	------	-----------	--	-----