

# TCH 125 Centrifugal Pump



200 Newsome Drive  
Yorktown, VA 23693  
1-800-535-4243  
www.Travaini.com



<b>Head Capacity</b>	25 to 175 Feet
<b>Capacity</b>	Up to 1680 USGPM
<b>Features</b>	Oversized alloy shaft to minimize deflection and vibrations
<b>Shaft Sealing</b>	Mechanical seal (standard) Double mechanical seal Packed Stuffing box
<b>Options</b>	Bareshaft Pump Coupled to electric motor Monoblock
<b>Temperature</b>	GS & RA: -20°C-280°C A3, HC, & DU: -40°C-280°C

## Technical Data

PUMP TYPE		TCH125-250	TCH125-315
Head, max	Ft	115	174
Capacity, max	GPM	1680	1530
Speed	RPM	1750	1750

## Standard Materials of Construction\*\*

Part No.	Description	GS	RA	A3	HC	DU
102	Pump casing	Ductile iron			Hastealloy C	ASTM-CN7M
135	Wear plates	-	Cast iron			
161	Casing cover	Ductile iron				
210	Shaft	Stainless steel AISI 316				Incoloy 825
230	Impeller					ASTM-CN7M
330	Bearing housing	Cast iron				
524	Shaft sleeve	Stainless steel AISI 316			Hastealloy C	Incoloy 825

## Model Designation

TCH125-250 A/1X-C/A3	
T	Travaini manufacturer
C	Monostage centrifugal pump
H	Closed impeller
125	Discharge flange size (mm)
250	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
1X	Constructive project number
C	Shaft Sealing: C—single mechanical seal 2C— Double mechanical seal
A3	Materials of construction

\*\*Special Materials Available Upon Request  
--For further information please consult Travaini Pumps USA.

REF:	JGJ/RR	Date	3/30/2015	Nº:	100274.000
------	--------	------	-----------	-----	------------