

TCT 100 Centrifugal Pump



200 Newsome Drive
Yorktown, VA 23693
1-800-535-4243
www.Travaini.com



Head Capacity	32-565 Feet
Capacity	Up to 900 GPM
Features	Semi-open impeller design allows for the handling of viscous liquids
Shaft Sealing	Mechanical seal (std.) Double mechanical seal Packed stuffing box
Options	Bareshaft pump Coupled to electric motor Spacer coupling Monoblock
Temperature	GS & RA: -20°C-280°C A3, HC, & DU: -40°C-280°C

Technical Data

PUMP TYPE		TCT100-200
Head, max	Ft	56
Capacity, max	GPM	900
Speed	RPM	1750

Standard Materials of Construction**

Part No.	Description	GS	RA	A3	HC	DU	
102	Pump casing	Ductile iron			Hastelloy C	ASTM-CN7M	
135	Wear plates	-	Cast iron				
161	Casing cover	Ductile iron					
210	Shaft	Stainless steel AISI 316				Incoloy 825	
230	Impeller					ASTM-CN7M	
330	Bearing housing	Cast iron					
524	Shaft sleeve	Stainless steel AISI 316			Hastelloy C	Incoloy 825	

Model Designation

TCT100-200 A/1X-C/A3	
T	Travaini manufacturer
C	Monostage centrifugal pump
T	Open vortex impeller
100	Discharge flange size (mm)
200	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
1X	Constructive project number
C	Shaft sealing: C—Single mechanical seal 2C— Double mechanical seal
A3	Materials of construction

**Special Materials Available Upon Request
--For further information please consult Travaini Pumps USA.

REF:	JGJ/RR	Date	3/17/2015	Nº:	100435.000
------	--------	------	-----------	-----	------------