

TRSE125
Single Stage
Liquid Ring Compressor



200 Newsome Drive
 Yorktown, VA 23693
 1-800-535-4243
 www.Travaini.com



Pressure Range	4 to 20 PSig
Capacity	600-1050 CFM
Features	Single stage vacuum pump with external sealed bearings
Shaft Sealing Options	Mechanical seals (Double mechanical seals or stuffing box optional)
Options	Bareshaft pump Coupled to electric motor V-Belt driven
Optional Accessories	Available as a component in larger assembly

Technical Data

PUMP TYPE		TRSE125-1250	TRSE125-1550
Speed	RPM	1180	1180
Motor - installed power	HP	100	100
Average service liquid flow	GPM	30	80
Noise level at 150 Torr	dB(A)		
Maximum Pressure	PSig	20	10

Standard Materials of Construction**

Part No.	Description	F	RX	RA	A3
106	Suction casing	Cast iron			Stainless steel AISI 316
107	Discharge casing				
110	Impeller housing				
210	Shaft	Stainless steel AISI 420	Stainless steel AISI 316		
357	Bearing housing	Cast iron			
230	Impeller	Ductile iron	Stainless steel AISI 304	Stainless steel AISI 316	

Model Designation

TRSC125-1550/C/RA	
T	Travaini manufacturer
R	Liquid ring pump
S	Single stage pump
C	Design revision
125	Flange size (mm)
1550	Nominal capacity (m ³ /hr)*
C	Shaft sealing: C = Mechanical seal C2=Double mechanical seal B = Packing seal
RA	Materials of construction (see table)

*Applies to vacuum systems

**Special materials available upon request

-Request for information on our WATERSEAL and DYNASEAL engineered vacuum systems

-For further information please consult Travaini Pumps USA.

REF:	JGJ/	Date	4/23/2015	Nº:	101004.000
------	------	------	-----------	-----	------------