TRVA 50 Single Stage Liquid Ring Vacuum Pump



200 Newsome Drive Yorktown, VA 23693 1-800-535-4243 www.Travaini.com



Pressure Range	25 to 760 TORR
Capacity	35 to 145 CFM
Features	Single stage vacuum pump mounted on motor shaft.
Shaft sealing options	Mechanical seal
Options	Monoblock with electric motor
Accessories	Available as a component in a larger assembly

Technical Data

PUMP TYF	PE	TRVA 50-220		
Speed	RPM	1750		
Motor - installed power	HP	10		
Avg. service liquid flow	GPM	6		
Noise level at 150 Torr	dB(A)	72		
Max. Vacuum	Torr	25		

Standard Materials of Construction**

Part No.	Description	GH
106	Suction casing	
107	Discharge casing	Cast Iron
110	Impeller housing	
210	Shaft	Stainless Steel AISI 304
357	Bearing housing	Cast Iron
230	Impeller	Stainless Steel AISI 420

Model Designation

TRVA50-220/C/RX		
T	Travaini manufacturer	
R	Liquid ring pump	
٧	Vari-port design	
Α	Design revision	
50	Flange size (mm)	
220	Nominal capacity (m³/hr)	
С	C = Mechanical seal	
GH	Materials of construction (see table)	

⁻For further information please consult Travaini Pumps USA.

REF: JM/CGZ Date: 8/14/19	N°:
---------------------------	-----

^{**}Special materials available upon request
-Request for information on our WATERSEAL and DYNASEAL engineered vacuum systems