TRVX1000 Single Stage Liquid Ring Vacuum Pump



200 Newsome Drive Yorktown, VA 23693 1-800-535-4243 www.Travaini.com



Pressure Range	25 to 760 TORR	
Capacity	140 to 590 CFM	
Features	Single-Stage vacuum pump with external bearings, vari-port design	
Shaft Sealing Options	Mechanical seal (standard) Double mechanical seal Stuffing box	
Options	Bareshaft pump Coupled to electric motor Monoblock	
Optional Accessories	Available as a component in larger assembly	

Technical Data

PUMP TYPE		TRVX1003	TRVX1005	TRVX1007
Speed	RPM	1750	1750	1750
Motor - installed power	HP	30	40	40
Average service liquid flow	GPM	8	10	11
Noise level at 150 Torr	dB(A)	73	73	73
Minimum suction pressure	Torr	25	25	25

Standard Materials of Construction**

Part No.	Description	F	RX	RA	A3
106	Suction casing				
107	Discharge casing	Cast iron		Ctaipless stool	
110	Impeller housing		Sto		Stainless steel AISI 316
210	Shaft	Stainless steel AISI 420 Stainless steel AISI 316			
357	Bearing housing	Cast iron			
230	Impeller	Ductile iron Stainless steel AISI 304 Stainless steel AISI 316			

Model Designation

TRVX1007/C/RA		
T	Travaini manufacturer	
R	Liquid ring pump	
٧	Single stage vacuum pump With vari-port design	
Х	Design revision	
100	Flange size (mm)	
7	Hydraulic size	
С	Shaft sealing: C = Mechanical seal C2 = Double mechanical seal B = Packing seal	
RA	Materials of construction (see table)	

⁻For further information please consult Travaini Pumps USA.

REF: JGJ/RK Date 1/19/2015	N°: 100952.000
----------------------------	----------------

^{**}Special materials available upon request

⁻Request for information on our WATERSEAL and DYNASEAL engineered vacuum systems